

HOWO-NX

8X4 CARGO TRUCK CHASSIS

350HP Maks Torsi
1388 Nm pada 1200-1600 rpm

NX-350CG



WE AIM AT CUSTOMERS MAXIMUM SATISFACTION



Tata letak di dalam kabin ditata dengan baik dengan desain ergonomis tingkat tinggi



Kursi airbag yang nyaman dengan bantalan sandaran



Sakelar instrumen dan sakelar pintu ditata secara apik



Desain terpadu yang ergonomis dari sabuk pengaman dan kursi menghindari sensasi tercekik pada pengemudi yang disebabkan oleh pengereman darurat



Kaca spion berfitur lengkap dengan penyetelan elektrik menjamin kendaraan dapat beroperasi dalam berbagai kondisi kerja dari berbagai sudut pandang



Pedal naik anti selip dan pintu dengan bukaan 90° memudahkan pengemudi untuk masuk ke dalam

* Untuk meningkatkan mutu dan penyesuaian dengan perkembangan teknologi, spesifikasi dapat berubah sewaktu-waktu tanpa pemberitahuan.



EURO 5
Emission Standard

LAYANAN KONSUMEN
Phone : 021 2309 0095
WhatsApp : 0811 7670 761
Email : care@masautomobil.co.id

1 Tahun GARANSI
atau 100.000 Km
mana yang terlewat akan dikawatir

www.masautomobil.co.id

Agen Pemegang Merek & Distributor :
PT Mas Automobil Sejahtera

SPESIFIKASI TEKNIS

SPESIFIKASI		NX-350CG		
Driving Type / Jenis Penggerak		8 x 4		
DIMENSI / DIMENSION				
Panjang / Overall Length [OAL]	mm	11.995		
Lebar / Overall Width [OW]	mm	2.495		
Tinggi / Overall Height [OH]	mm	3.150		
Jarak Sumbu / Wheelbase [WB]	mm	1.800 + 4.600 + 1.350		
Julur Depan / Front Overhang [FOH]	mm	1.550		
Julur Belakang / Rear Overhang [ROH]	mm	2.695		
Jarak Terendah ke Tanah / Minimum Clearance [HH]	mm	260		
Jejak Depan / Front Tread [AW]	mm	2.022		
Jejak Belakang / Rear Tread [CW]	mm	1.860		
MESIN / ENGINE				
Model		MC07H.35-50		
Tipe / Type		4 Stroke Direct Injection Diesel Engine 6 cylinder in line with water cooling, Intercooler Turbocharged		
Sistem Kontrol Emisi		EURO 5		
Jumlah Silinder / No. of Cylinders		6		
Diameter x Langkah / Bore x Stroke	mm	108 X 134		
Isi Silinder / Piston Displacement	cc	7.360		
Tenaga Maksimum / Maximum Power	HP/rpm	350 / 2.200		
Torsi Maksimum / Maximum Torque	Nm/rpm	1.388 / 1.200 - 1.600		
KOPLING / CLUTCH				
Tipe/Type		Single dry plate, Diaphragm-spring clutch, Hydraulically operating with air assistance		
Diameter / Diameter		430		
TRANSMISI / TRANSMISSION				
Model		HW13709XSTC2		
Perbandingan Gigi / Gear Ratio	1st	10th	11.000	-
	2nd	11th	6.634	-
	3rd	12th	4.810	-
	4th	13th	3.484	-
	5th	14th	2.659	-
	6th	15th	1.904	-
	7th	16th	1.381	-
	8th	R2	1.000	-
	9th		0.763	-
	Reverse		10.078	
BERAT / WEIGHT				
Berat Kosong Kendaraan / Curb Weight	kg	11.690		
Berat Total Kendaraan / Gross Vehicle Weight (GVW)	kg	40.000		
Kapasitas Gardan Depan / Capacity Front Axle	kg	7.000 x 2		
Kapasitas Gardan Belakang / Capacity Rear Axle	kg	13.000 x 2		
REM / BRAKE				
Tipe/Type		Full Air Brake		
Rem Kaki / Service Brake		Dual circuit compressed air brake		
Rem Tangan / Hand Brake / Parking Brake		Spring energy, compressed air operating on rear wheels		
Rem Pembantu / Auxiliary Brake		Engine exhaust valve brake, hydraulic retarder		
Anti-lock Braking System (ABS)		Yes		
RODA / TYRE				
Ukuran Ban		11.00R20		
Ukuran Velg		8.25V-20		
SUMBU / AXLE				
Depan / Front		VGD71 (2x7 Ton)		
Belakang / Rear		MCJ13JGY (2x13 Ton)		
LAIN-LAIN / OTHERS				
Kapasitas Tangki / Fuel Tank Capacity	ltr	400		
Radius Putar Minimum / Minimum Turning Radius	m	13.8		
Daya Tanjak Maksimum / Maximum Gradeability	%	20		
Kecepatan Maksimum / Maximum Speed	km/h	102		
Kelistrikan / Electrics		Operating voltage: 24 V, negative grounded Starter, Alternator, Batteries, Cigar-lighter, horn, headlamps, fog lights, brake lights, indicators and reverse light		
Garansi / Warranty		1 Tahun / 100,000 km		
SASIS & RANGKA / CHASSIS & FRAME				
Rangka / Frame		Double layer frame		
Ukuran Rangka / Frame Dimensions		300x80x(8+5)		
SUSPENSI / SUSPENSION				
Depan / Front		10 layer Semi-elliptic leaf springs, With hydraulic telescopic double-action shock absorbers		
Belakang / Rear		12 layer Semi-elliptic leaf springs, with bogie spring & stabilizer		
* Untuk meningkatkan mutu dan penyesuaian dengan perkembangan teknologi, spesifikasi dapat berubah sewaktu-waktu tanpa pemberitahuan.				
** The manufacturer reserves the right of technical alteration/change for better improvement without prior notice!				