

# HOWO-NX

6X4 CARGO LONG CHASSIS

**360HP** Maks Torsi  
1800 Nm pada 1000-1400 rpm

**NX-360CGL**



WE AIM AT CUSTOMERS MAXIMUM SATISFACTION



Tata letak di dalam kabin ditata dengan baik dengan desain ergonomis tingkat tinggi



Kursi airbag yang nyaman dengan bantalan sandaran



Sakelar instrumen dan sakelar pintu ditata secara apik



Desain terpadu yang ergonomis dari sabuk pengaman dan kursi menghindari sensasi tercekik pada pengemudi yang disebabkan oleh pengereman darurat



Kaca spion berfitur lengkap dengan penyetelan elektrik menjamin kendaraan dapat beroperasi dalam berbagai kondisi kerja dari berbagai sudut pandang



Pedal naik anti selip dan pintu dengan bukaan 90° memudahkan pengemudi untuk masuk ke dalam

\* Untuk meningkatkan mutu dan penyesuaian dengan perkembangan teknologi, spesifikasi dapat berubah sewaktu-waktu tanpa pemberitahuan.



[www.masautomobil.co.id](http://www.masautomobil.co.id)

Agan Pemegang Merek & Distributor :  
**PT Mas Automobil Sejahtera**

# SPESIFIKASI TEKNIS

SPESIFIKASI		NX-360CGL		
Driving Type / Jenis Penggerak		6 x 4		
<b>DIMENSI / DIMENSION</b>				
Panjang / Overall Length [OAL]	mm	11.950		
Lebar / Overall Width [OW]	mm	2.494		
Tinggi / Overall Height [OH]	mm	3.138		
Jarak Sumbu / Wheelbase [WB]	mm	5.825 + 1.350		
Julur Depan / Front Overhang [FOH]	mm	1.550		
Julur Belakang / Rear Overhang [ROH]	mm	3.225		
Jarak Terendah ke Tanah / Minimum Clearance [HH]	mm	260		
Jejak Depan / Front Tread [AW]	mm	2.038		
Jejak Belakang / Rear Tread [CW]	mm	1.858		
<b>MESIN / ENGINE</b>				
Model		MC11.36-50		
Tipe / Type		4 Stroke Direct Injection Diesel Engine 6 cylinder in line with water cooling, Intercooler Turbocharged		
Sistem Kontrol Emisi		EURO 5		
Jumlah Silinder / No. of Cylinders		6		
Diameter x Langkah / Bore x Stroke	mm	120 X 155		
Isi Silinder / Piston Displacement	cc	10.518		
Tenaga Maksimum / Maximum Power	HP/rpm	360 / 1.900		
Torsi Maksimum / Maximum Torque	Nm/rpm	1.800 / 1.000 - 1.400		
<b>KOPLING / CLUTCH</b>				
Tipe/Type		Single dry plate, Diaphragm-spring clutch, Hydraulically operating with air assistance		
Diameter / Diameter		430		
<b>TRANSMISI / TRANSMISSION</b>				
Model		HW19709XSTL		
Perbandingan Gigi / Gear Ratio	1st	10th	15.280	-
	2nd	11th	12.470	-
	3rd	12th	8.790	-
	4th	13th	6.170	-
	5th	14th	4.375	-
	6th	15th	2.850	-
	7th	16th	2.010	-
	8th	R2	1.410	-
	9th		1.000	-
	Reverse		14.060	
<b>BERAT / WEIGHT</b>				
Berat Kosong Kendaraan / Curb Weight	kg	10.200		
Berat Total Kendaraan / Gross Vehicle Weight (GVW)	kg	41.500		
Kapasitas Gardan Depan / Capacity Front Axle	kg	9.500		
Kapasitas Gardan Belakang / Capacity Rear Axle	kg	16.000 x 2		
<b>REM / BRAKE</b>				
Tipe/Type		Full Air Brake		
Rem Kaki / Service Brake		Dual circuit compressed air brake		
Rem Tangan / Hand Brake / Parking Brake		Spring energy, compressed air operating on rear wheels		
Rem Pembantu / Auxiliary Brake		Engine exhaust valve brake, hydraulic retarder		
Anti-lock Braking System (ABS)		Yes		
<b>RODA / TYRE</b>				
Ukuran Ban		11.00R20		
Ukuran Velg		8.0-20		
<b>SUMBU / AXLE</b>				
Depan / Front		VGD95 (9.5 Ton)		
Belakang / Rear		MCP16ZG (2x16 Ton)		
<b>LAIN-LAIN / OTHERS</b>				
Kapasitas Tangki / Fuel Tank Capacity	ltr	400		
Radius Putar Minimum / Minimum Turning Radius	m	13.5		
Daya Tanjak Maksimum / Maximum Gradeability	%	30		
Kecepatan Maksimum / Maximum Speed	km/h	60		
Kelistrikan / Electrics		Operating voltage: 24 V, negative grounded Starter, Alternator, Batteries, Cigar-lighter, horn, headlamps, fog lights, brake lights, indicators and reverse light		
Garansi / Warranty		1 Tahun / 100,000 km		
<b>SASIS &amp; RANGKA / CHASSIS &amp; FRAME</b>				
Rangka / Frame		Double layer frame		
Ukuran Rangka / Frame Dimensions		300x80x(8+5)		
<b>SUSPENSI / SUSPENSION</b>				
Depan / Front		10 layer Semi-elliptic leaf springs, With hydraulic telescopic double-action shock absorbers		
Belakang / Rear		12 layer Semi-elliptic leaf springs, with bogie spring & stabilizer		
* Untuk meningkatkan mutu dan penyesuaian dengan perkembangan teknologi, spesifikasi dapat berubah sewaktu-waktu tanpa pemberitahuan.				
** The manufacturer reserves the right of technical alteration/change for better improvement without prior notice!				