

HOWO-NX

6X4 TRACTOR HEAD

360HP Maks Torsi
1800 Nm pada 1000-1400 rpm

NX-360TH



WE AIM AT CUSTOMERS MAXIMUM SATISFACTION



Tata letak di dalam kabin ditata dengan baik dengan desain ergonomis tingkat tinggi



Kursi airbag yang nyaman dengan bantalan sandaran



Sakelar instrumen dan sakelar pintu ditata secara apik



Desain terpadu yang ergonomis dari sabuk pengaman dan kursi menghindari sensasi tercekik pada pengemudi yang disebabkan oleh pengereman darurat



Kaca spion berfitur lengkap dengan penyetelan elektrik menjamin kendaraan dapat beroperasi dalam berbagai kondisi kerja dari berbagai sudut pandang



Pedal naik anti selip dan pintu dengan bukaan 90° memudahkan pengemudi untuk masuk ke dalam

* Untuk meningkatkan mutu dan penyesuaian dengan perkembangan teknologi, spesifikasi dapat berubah sewaktu-waktu tanpa pemberitahuan.



www.masautomobil.co.id

Agen Pemegang Merek & Distributor :
PT Mas Automobil Sejahtera

SPESIFIKASI TEKNIS

SPESIFIKASI		NX-360TH	
Driving Type / Jenis Penggerak		6 x 4	
DIMENSI / DIMENSION			
Panjang / Overall Length [OAL]	mm	6.850	
Lebar / Overall Width [OW]	mm	2.500	
Tinggi / Overall Height [OH]	mm	3.055	
Jarak Sumbu / Wheelbase [WB]	mm	3.225 + 1.350	
Julur Depan / Front Overhang [FOH]	mm	1.550	
Julur Belakang / Rear Overhang [ROH]	mm	720	
Jarak Terendah ke Tanah / Minimum Clearance [HH]	mm	238	
Jejak Depan / Front Tread [AW]	mm	2.030	
Jejak Belakang / Rear Tread [CW]	mm	1.860	
MESIN / ENGINE			
Model		MC11.36-50	
Tipe / Type		4 Stroke Direct Injection Diesel Engine 6 cylinder in line with water cooling, Intercooler Turbocharged	
Sistem Kontrol Emisi		EURO 5	
Jumlah Silinder / No. of Cylinders		6	
Diameter x Langkah / Bore x Stroke	mm	120 X 155	
Isi Silinder / Piston Displacement	cc	10.518	
Tenaga Maksimum / Maximum Power	HP/rpm	360 / 1.900	
Torsi Maksimum / Maximum Torque	Nm/rpm	1.800 / 1.000 - 1.400	
KOPLING / CLUTCH			
Tipe/Type		Single dry plate, Diaphragm-spring clutch, Hydraulically operating with air assistance	
Diameter / Diameter		430	
TRANSMISI / TRANSMISSION			
Model		HW13709XST	
Perbandingan Gigi / Gear Ratio	1st 10th	15.280	-
	2nd 11th	12.469	-
	3rd 12th	8.792	-
	4th 13th	6.169	-
	5th 14th	4.375	-
	6th 15th	2.850	-
	7th 16th	2.010	-
	8th R2	1.410	-
	9th	1.000	-
	Reverse	14.058	-
BERAT / WEIGHT			
Berat Kosong Kendaraan / Curb Weight	kg	8.800	
Berat Total Kendaraan / Gross Vehicle Weight (GVW)	kg	60.000	
Kapasitas Gardan Depan / Capacity Front Axle	kg	7.000	
Kapasitas Gardan Belakang / Capacity Rear Axle	kg	13.000 x 2	
REM / BRAKE			
Tipe/Type		Full Air Brake	
Rem Kaki / Service Brake		Dual circuit compressed air brake	
Rem Tangan / Hand Brake / Parking Brake		Spring energy, compressed air operating on rear wheels	
Rem Pembantu / Auxiliary Brake		Engine exhaust valve brake, Hydraulic retarder	
Anti-lock Braking System (ABS)		Yes	
RODA / TYRE			
Ukuran Ban		11.00R20	
Ukuran Velg		8.0-20	
SUMBU / AXLE			
Depan / Front		VGD71 (7 Ton)	
Belakang / Rear		MCY13BGS (2x13 Ton)	
LAIN-LAIN / OTHERS			
Kapasitas Tangki / Fuel Tank Capacity	ltr	600	
Radius Putar Minimum / Minimum Turning Radius	m	7.5	
Daya Tanjak Maksimum / Maximum Gradeability	%	44.9	
Kecepatan Maksimum / Maximum Speed	km/h	82	
Kelistrikan / Electrics		Operating voltage: 24 V, negative grounded Starter, Alternator, Batteries Cigar-lighter, horn, headlamps, fog lights, brake lights, indicators and reverse light	
Garansi / Warranty		1 Tahun / 100,000 km	
SASIS & RANGKA / CHASSIS & FRAME			
Rangka / Frame		Double layer frame	
Ukuran Rangka / Frame Dimensions	mm	300x80x(8+5)	
Fifth Wheel	inch	2	
SUSPENSII / SUSPENSION			
Depan / Front		Semi-elliptic leaf springs With hydraulic telescopic double-action shock absorbers	
Belakang / Rear		Semi-elliptic leaf springs	
* Untuk meningkatkan mutu dan penyesuaian dengan perkembangan teknologi, spesifikasi dapat berubah sewaktu-waktu tanpa pemberitahuan. ** The manufacturer reserves the right of technical alteration/change for better improvement without prior notice!			