

HOWO-NX

6X4 TRACTOR HEAD

440HP Maks Torsi
2100 Nm pada 1000-1400 rpm

NX-440TH



WE AIM AT CUSTOMERS MAXIMUM SATISFACTION



Tata letak di dalam kabin ditata dengan baik dengan desain ergonomis tingkat tinggi



Kursi airbag yang nyaman dengan bantalan sandaran



Sakelar instrumen dan sakelar pintu ditata secara apik



Desain terpadu yang ergonomis dari sabuk pengaman dan kursi menghindari sensasi tercekik pada pengemudi yang disebabkan oleh pengereman darurat



Kaca spion berfitur lengkap dengan penyetelan elektrik menjamin kendaraan dapat beroperasi dalam berbagai kondisi kerja dari berbagai sudut pandang



Pedal naik anti selip dan pintu dengan bukaan 90° memudahkan pengemudi untuk masuk ke dalam

* Untuk meningkatkan mutu dan penyesuaian dengan perkembangan teknologi, spesifikasi dapat berubah sewaktu-waktu tanpa pemberitahuan.



EURO 5
Emission Standard

LAYANAN KONSUMEN
Phone : 021 2309 0095
WhatsApp : 0811 7670 761
Email : care@masautomobil.co.id

1 Tahun GARANSI
atau 100.000 Km
maksud yang terpanjang sesuai ketentuan

www.masautomobil.co.id

Agen Pemegang Merek & Distributor :
PT Mas Automobil Sejahtera

SPESIFIKASI TEKNIS

SPESIFIKASI		NX-440TH	
Driving Type / Jenis Penggerak		6 x 4	
DIMENSI / DIMENSION			
Panjang / Overall Length [OAL]	mm	6.850	
Lebar / Overall Width [OW]	mm	2.550	
Tinggi / Overall Height [OH]	mm	3.500	
Jarak Sumbu / Wheelbase [WB]	mm	3.225 + 1.350	
Julur Depan / Front Overhang [FOH]	mm	1.550	
Julur Belakang / Rear Overhang [ROH]	mm	720	
Jarak Terendah ke Tanah / Minimum Clearance [HH]	mm	238	
Jejak Depan / Front Tread [AW]	mm	2.030	
Jejak Belakang / Rear Tread [CW]	mm	1.860	
MESIN / ENGINE			
Model		MC11.44-50	
Tipe / Type		4 Stroke Direct Injection Diesel Engine 6 cylinder in line with water cooling, Intercooler Turbocharged	
Sistem Kontrol Emisi		EURO 5	
Jumlah Silinder / No. of Cylinders		6	
Diameter x Langkah / Bore x Stroke	mm	120 X 155	
Isi Silinder / Piston Displacement		10.518	
Tenaga Maksimum / Maximum Power	HP/rpm	440 / 1.900	
Torsi Maksimum / Maximum Torque	Nm/rpm	2.100 / 1.000 - 1.400	
KOPLING / CLUTCH			
Tipe/Type		Single dry plate, Diaphragm-spring clutch, Hydraulically operating with air assistance	
Diameter / Diameter		430	
TRANSMISI / TRANSMISSION			
Model		HW25712XSTC	
Perbandingan Gigi / Gear Ratio	1st 10th	11.679	1.266
	2nd 11th	9.091	1.000
	3rd 12th	7.036	0.783
	4th 13th	5.468	-
	5th 14th	4.318	-
	6th 15th	3.381	-
	7th 16th	2.709	-
	8th R2	2.105	2.384
	9th	1.629	-
	Reverse	10.294	-
BERAT / WEIGHT			
Berat Kosong Kendaraan / Curb Weight	kg	8.800	
Berat Total Kendaraan / Gross Vehicle Weight (GVW)	kg	70.000	
Kapasitas Gardan Depan / Capacity Front Axle	kg	9.500	
Kapasitas Gardan Belakang / Capacity Rear Axle	kg	16.000 x 2	
REM / BRAKE			
Tipe/Type		Full Air Brake	
Rem Kaki / Service Brake		Dual circuit compressed air brake	
Rem Tangan / Hand Brake / Parking Brake		Spring energy, compressed air operating on rear wheels	
Rem Pembantu / Auxiliary Brake		Engine exhaust valve brake	
Anti-lock Braking System (ABS)		Yes	
RODA / TYRE			
Ukuran Ban		12.00R24	
Ukuran Velg		8.5-24	
SUMBU / AXLE			
Depan / Front		MVP09 (9 Ton)	
Belakang / Rear		MCP16 (2x16 Ton)	
LAIN-LAIN / OTHERS			
Kapasitas Tangki / Fuel Tank Capacity		600	
Radius Putar Minimum / Minimum Turning Radius		11	
Daya Tanjak Maksimum / Maximum Gradeability		44	
Kecepatan Maksimum / Maximum Speed		86	
Kelistrikan / Electrics		Operating voltage: 24 V, negative grounded Starter, Alternator, Batteries Cigar-lighter, horn, headlamps, fog lights, brake lights, indicators and reverse light	
Garansi / Warranty		1 Tahun / 100,000 km	
SASIS & RANGKA / CHASSIS & FRAME			
Rangka / Frame		Double layer frame	
Ukuran Rangka / Frame Dimensions		300x80x(8+8)	
Fifth Wheel		2	
SUSPENSIF / SUSPENSION			
Depan / Front		Semi-elliptic leaf springs With hydraulic telescopic double-action shock absorbers	
Belakang / Rear		Semi-elliptic leaf springs	
* Untuk meningkatkan mutu dan penyesuaian dengan perkembangan teknologi, spesifikasi dapat berubah sewaktu-waktu tanpa pemberitahuan. ** The manufacturer reserves the right of technical alteration/change for better improvement without prior notice!			